



COMMERCIAL MOBILE GENERATORS

Innovative Reliability for Mobile Power Applications



The Cummins Onan mission is simple: Design and create the best, most innovative commercial mobile generator sets and power products in the industry. Since we're Cummins Onan, we can do no less.

The Global Leader for a Reason



Performance you rely on

The Cummins Onan brand of generators continues our tradition of dependable performance, innovative technologies, and an ongoing commitment to provide you with the best power generation products available worldwide.

Plus, you can rest assured that after you purchase a Cummins Onan generator, our global customer support network will continue to provide you with high-quality parts, products, expert sales assistance and superior service.

More than 70 years of generator experience means that Cummins Onan generators meet your toughest demands for rugged applications where reliability, uptime and peak performance are crucial for success. That's why Cummins Onan is already the global leader. Our complete line of 2-40 kW mobile power products include diesel, gasoline, LP, hydraulic and PTO power options.





FIRE/RESCUE Maximum Power, Minimal Space

Fire trucks need to carry a lot of equipment

in limited space. Our engineers are constantly developing new ways to help you put more power into your vehicle without taking up more space.

Cummins Onan hydraulic and PTO generators fit into compartments a fraction of the size needed for diesel generators. Our complete line of generators is designed to provide you with reliable power, quiet operation, easy maintenance and compact installation. For maximum power in minimal space, no one sizes up to the efficiency of Cummins Onan generators. We back this up with an excellent warranty and dependable service network.

RELIABILITY

"The Onan generator on our '85 fire truck has served us well, but the new Cummins Onan model we installed is really a step up, and fit easily in the housing with room to spare. Cummins Onan also provides the reliable backup power we needed for Fire/EMS/PW radio transmission equipment using 200 amp service with a 100 amp emergency panel and transfer switch."







TELECOM/UTILITY Heavy-Duty, Field-Proven

In the field, it simply has to work right, every time.

Cummins Onan delivers for utility and telecom fleets with heavy-duty, field-proven generators designed for long life. Our EFI technology Quiet Gasoline[™] generators feature exceptionally low noise and vibration, easy installation and diagnostic capability. And, our advanced digital control system maintains precise voltage and frequency stability as loads change.

POWER

"Our service trucks demand a lot of power. The Cummins Onan generator handles the 5000-watt electric heater, 300 watts of lights, 5-hp compressor and everything else we throw at it without missing a beat."









MOBILE SPECIALTY Power on the Move

Cummins Onan offers a wide selection of generators for mobile vehicle applications from broadcast, emergency management and surveillance activities, to medical or other critical services, food preparation, or simply for recreational enjoyment. Both our gasoline and diesel platforms feature Cummins Onan quiet operation and reliability, in a wide range from commercial portable sets to heavy-duty generators where low noise and low vibration are required.

QUALITY

"As I was looking for a generator to put on a Public Safety Command Trailer, Cummins Onan was recommended time and again. I have not been disappointed — I needed 120v single phase capable of doing a steady 60 amps, and it performs flawlessly."

Peace of Mind

Largest Support Network

Developed, manufactured and serviced by one company, Cummins Onan generator sets are supported by the largest and best-trained worldwide certified distributor/dealer network in the industry. That means wherever you need mobile power, you can be confident that a Cummins Onan distributor/dealer is nearby. Since we have the largest network in the industry, genuine parts, quality service and expert installation assistance are easily obtained wherever you are, whenever you need them. Plus, our extensive training and certification process ensures you receive exceptional product service and support. It's simple to find us — just visit www.cumminsonan.com for the nearest Cummins Onan distributor/dealer.

Warranty

We're so confident about our mobile power generation products that all Cummins Onan products are covered by extensive, completely transferable warranties.

| Warranty Coverage | |
|--|-------------------------------|
| QG (5.5, 7.0 kW), SD, QD | 2 yrs/2000 hrs |
| QG (2.8, 4.0 kW) | 1 yr/1000 hrs |
| HG, PTO | 5 yrs/1000 hrs* |
| *Warranty on the HG/PTO covers (limited) travel to the | site for the first two years. |

To find warranty information for your model, consult the product specification sheet, see your Cummins Onan Distributor/Dealer, or visit www.cumminsonan.com.





Insist on the Quality of Green Label Parts

Specifically designed by Cummins Onan for Cummins Onan generators, Green Label replacement and maintenance products provide dependable power and performance for the life of your generator. For genuine Green Label air filters, spark plugs, oil filters, tune-up kits and more, see your Cummins Onan authorized service and parts dealer. To locate the dealer nearest you, visit www.cumminsonan.com.

Commercial Mobile Accessories

Accessories such as tailpipes, remote panels & harnesses, muffler kits and more are available through your local Cummins Onan dealer/distributor. To download an accessories catalog, visit www.cumminsonan.com/cm/products/accessories/.

Product Line

We offer a complete line of mobile power products including generators from 2–40 kW. Mobile power is available in hydraulic, diesel, gasoline, LP and PTO powered models.

Commercial Mobile Quiet Diesel Series

| Model | _ | kW | Hz | Voltage | Amps | dB(A) | Ph | Length x Width x Height in/mm | Weight Ibs/kg |
|-----------------------|---------|------|---------|---------|-----------|-------|----|----------------------------------|------------------|
| | QD5000 | 4.8 | 50 | 230 | 21 | 68 | 1 | 34/876 x 23/581 x 20/515 | 400/181 |
| and the second second | | 5 | 60 | 120/240 | 41.7/20.8 | | 1 | | |
| | 5 | 60 | 120/240 | 12 | | 3 | | | |
| the second second | QD6000 | 6 | 60 | 120 | 50 | 69 | 1 | 36/923 x 24/615 x 22/566 | 420/191 |
| | QD6500 | 6.25 | 60 | 100 | 63 | 71 | 1 | 36/923 x 24/615 x 22/566 | 420/191 |
| | QD7500 | 7.5 | 60 | 120 | 62.5 | 71 | 1 | 36/923 x 24/615 x 22/566 | 420/191 |
| | QD8000 | 8 | 60 | 120 | 66.6 | 72 | 1 | 36/923 x 24/615 x 22/566 | 420/191 |
| | | | 50 | 230 | 35 | 67 | 1 | 41/1053 x 25/621 x 27/686 | 816/370 |
| | QD10000 | 10 | 60 | 120/240 | 83.3/41.7 | 68 | 1 | 41/1053 x 25/621 x 27/686 | 816/370 |
| e c | QD12000 | 12 | 60 | 120/240 | 100/50 | 68 | 1 | 41/1053 x 25/621 x 27/686 | 816/370 |

Commercial Mobile Quiet Diesel Series – Remote Radiator

| Model | kW | Hz | Voltage | Amps | dB(A) | Ph | Length x Width x Height in/mm | <mark>Weight</mark> Ibs/kg |
|---------|------|----|---|--|-------|--|----------------------------------|-------------------------------|
| QD7000 | 7 | 50 | 110/220 115/230 120/240 220 230 | 63.6/31.8 60.9/30.4 58.3/29.2 31.8 30.4 | 60 | 1 1 1 1 | 36/914 x 22/559 x 23/584 | 601/272 |
| QD9500 | 9.5 | 50 | 110/220 115/230 120/240 220 230 | 86.4/43.2 82.6/41.3 79.2/39.6 43.2 41.3 | 62 | 1 1 1 1 | 41/1041 x 22/559 x 23/584 | 695/315 |
| QD11000 | 11 | 50 | 110/220 115/230 120/240 220 230 | 100/50 95.7/47.8 91.7/46 50 47.8 | 62 | 1 1 1 1 | 41/1041 x 22/559 x 23/584 | 695/315 |
| QD13500 | 13.5 | 50 | 110/220 115/230 120/240 220 230 110/220 115/230 120/240 220/380 230/400 240/416 | 122.7/61.4 117.4/58.7 112.5/56.3 61.4 58.7 44.3 42.4 40.6 25.6 24.4 23.4 | 63 | 1 1 1 3 3 3 3 3 3 3 3 3 | 45/1143 x 24/610 x 28/711 | 892/404 |

SPECIFICATIONS

Cummins Onan Commercial Mobile Generators

| Model | kW | Hz | Voltage | Amps | dB(A) | Ph | Length x Width x Height in/mm | <mark>Weight</mark> Ibs/kg |
|---------|------|----|---|--|-------|---|----------------------------------|-------------------------------|
| QD17500 | 17.5 | 50 | 110/220 115/230 120/240 220 230 110/220 115/230 120/240 220/380 230/400 240/416 | 159.1/79.5 152.2/76.1 145.8/72.9 79.5 76.1 57.4 54.9 52.6 33.2 31.6 30.4 | 63 | 1 1 1 3 3 3 3 3 3 3 3 3 3 | 45/1143 x 24/610 x 28/711 | 932/422 |
| QD19000 | 19 | 50 | 110/220 115/230 220 230 110/220 115/230 120/240 220/380 230/400 240/416 | 172.7/86.4 165.2/82.6 86.4 82.6 62.3 59.6 57.1 36.1 34.3 32.9 | 63 | 1 1 1 3 3 3 3 3 3 3 3 3 3 | 45/1143 x 24/610 x 28/711 | 932/422 |

Remote Radiator Specification*

| | Generator Cooling Package | | Size (in/mm) | |
|-------------------|---------------------------|--------|--------------|--------|
| | | L | W | Н |
| B Danta and a set | QD7000 | 17/430 | 14/368 | 20/508 |
| | QD9500 | 20/520 | 16/410 | 22/570 |
| | QD11000 | | | |
| V | QD13500 | | | |
| | QD17500 | 23/595 | 16/410 | 27/682 |
| | QD19000 | | | |

*Cummins Onan remote raditor and installation kit must be ordered with the generator. See specification sheet for cooling package installation details.

Commercial Mobile Standard Diesel Series

| Model | kW | Hz | Voltage | Amps | dB(A) | Ph | Length x Width x Height in/mm | <mark>Weight</mark> Ibs/kg |
|-------------|-----|----|---------------|-----------|-------|----|----------------------------------|-------------------------------|
| SD 6.0 | 6 | 50 | 115/230 | 52.1/26.1 | 75 | 1 | 37/942 x 21/533 x 24/610 | 491/223 |
| | | 60 | 120/240 | 50/25 | 76 | 1 | | |
| SD 7.5 | 7.5 | 60 | 120/240 | 62.5/31.3 | 76 | 1 | 37/940 x 21/533 x 24/610 | 491/223 |
| | | | 100/200 | 75/38 | | 1 | | |
| (Strength | | | Reconnectable | | | 3 | | |
| SD 8.0 | 8 | 50 | 115/230 | 70/35 | 76 | 1 | 39/1003 x 21/533 x 26/662 | 519/236 |
| | | | Reconnectable | | | 3 | 40/1028 x 21/533 x 26/662 | |
| SD 10.0 | 10 | 60 | 120/240 | 83/42 | 78 | 1 | 39/1003 x 21/533 x 26/662 | 519/236 |
| Antonia and | | | 100/200 | 100/50 | | 1 | | |
| | | | 120/240 | 30 | | 3 | 40/1028 x 21/533 x 26/662 | |
| SD 20.0 | 20 | 60 | 120/240 | 167/83 | 82 | 1 | 49/1245 x 24/610 x 28/711 | 890/404 |

Cummins Onan Commercial Mobile Generators

Commercial Mobile Quiet LP Series

| Model | | kW | Hz | Voltage | Amps | dB(A) | Ph | Length x Width x Height in/mm | <mark>Weight</mark> Ibs/kg |
|-------|--------|-----|----|---------|-----------|-------|----|----------------------------------|-------------------------------|
| | QG2000 | 2 | 50 | 230 | 8.7 | 70 | 1 | 22/559 x 16/417 x 13/330 | 125/57 |
| | QG2500 | 2.5 | 60 | 120 | 20.8 | 70 | 1 | 22/559 x 16/417 x 13/330 | 125/57 |
| | QG3300 | 3.3 | 50 | 115/230 | 28.7/14.3 | 65 | 1 | 31/775 x 21/523 x 16/417 | 174/83 |
| | QG3600 | 3.6 | 60 | 120 | 30 | 70 | 1 | 31/775 x 21/523 x 16/417 | 174/83 |
| 3 | QG5500 | 5.5 | 60 | 120 | 45.8 | 66 | 1 | 34/853 x 22/563 x 17/425 | 290/132 |
| · · | QG6500 | 6.5 | 60 | 120 | 54.2 | 70 | 1 | 34/853 x 22/563 x 17/425 | 290/132 |

Commercial Mobile Quiet Gasoline Series

| Model | kW | Hz | Voltage | Amps | dB(A) | Ph | Length x Width x Height in/mm | <mark>Weight</mark> Ibs/kg |
|--------|-----|-----|---------|-----------|-------|----|----------------------------------|-------------------------------|
| QG2300 | 2.3 | 50 | 230 | 10 | 70 | 1 | 22/559 x 16/417 x 13/330 | 125/57 |
| QG2800 | 2.8 | 60 | 120 | 23.3 | 70 | 1 | 22/559 x 16/417 x 13/330 | 125/57 |
| QG2800 | 2.8 | 60 | 100 | 28 | 70 | 1 | 22/559 x 16/417 x 13/330 | 125/57 |
| QG3600 | 3.6 | 50 | 115/230 | 31.3/15.7 | 65 | 1 | 31/775 x 21/523 x 16/417 | 174/83 |
| QG4000 | 4 | 60 | 120 | 33.3 | 70 | 1 | 31/775 x 21/523 x 16/417 | 174/83 |
| | | 100 | 40 | | | | | |
| QG5500 | 5.5 | 60 | 120/240 | 45.8/22.9 | 66 | 1 | 34/853 x 22/563 x 17/425 | 290/132 |
| | | | 120/240 | 13.2 | | 3 | | |
| QG7000 | 7 | 60 | 120/240 | 58.3/16.8 | 70 | 1 | 34/853 x 22/563 x 17/425 | 290/132 |
| | | | 120/240 | 16.8 | | 3 | | |

Cummins Onan Commercial Mobile Generators

Commercial Mobile Hydraulic Series

| Model | | kW | Hz | Voltage | Amps | dB(A) | Ph | Length x Width x Height in/mm | <mark>Weight</mark> Ibs/kg |
|-------|---------|----|----|---------|-----------|-------|----|----------------------------------|-------------------------------|
| | HG6000 | 6 | 60 | 120/240 | 50/25 | | 1 | 31/787 x 16/405 x 14/350 | 247/112 |
| | HG8000 | 8 | 50 | 115/230 | 69.6/34.8 | | 1 | 31/787 x 16/405 x 14/350 | 247/112 |
| | | | 60 | 120/240 | 67/33 | | 1 | 31/787 x 16/405 x 14/350 | 247/112 |
| | HG10000 | 10 | 60 | 120/240 | 83/42 | | 1 | 31/787 x 16/405 x 14/350 | 247/112 |
| | HG15000 | 15 | 60 | 120/240 | 125/63 | | 1 | 39/995 x 16/405 x 14/350 | 293/133 |
| | HG20000 | 20 | 60 | 120/240 | 166/83 | | 1 | 45/1133 x 19/490 x 17/439 | 680/309 |
| | HG25000 | 25 | 60 | 120/240 | 208/104 | | 1 | 45/1133 x 19/490 x 17/439 | 680/309 |

Commercial Mobile PTO Series

| Reconnectable 3 15 60 120/240 1 Reconnectable 3 3 20YD 16 50 115/230 1 27/686 x 14/350 x 15/381 35 20YD 16 50 115/230 1 27/686 x 14/350 x 15/381 35 20 60 120/240 1 3 36 20 60 120/240 1 3 36 20 50 115/230 1 28/711 x 14/350 x 15/381 38 Reconnectable 3 3 8 36 3 25 60 120/240 1 30 36 3 25 60 120/240 1 30 30 30 30 30 60 120/240 1 30/762 x 14/350 x 15/381 44 30 60 120/240 1 30/762 x 14/350 x 15/381 44 31 30/762 x 14/350 x 15/381 44 32 60 < | Model | | kW | Hz | Voltage | Amps | dB(A) | Ph | Length x Width x Height in/mm | <mark>Weight</mark> Ibs/kg |
|---|-------|------|----|----|---------------|------|-------|----|----------------------------------|-------------------------------|
| 15 60 120/240 1 Reconnectable 3 20YD 16 50 115/230 1 27/686 x 14/350 x 15/381 35 Reconnectable 3 3 3 3 3 3 20 60 120/240 1 3 3 3 20 60 120/240 1 3 3 3 20 60 120/240 1 3 3 3 25 60 115/230 1 28/711 x 14/350 x 15/381 38 Reconnectable 3 3 3 3 3 3 25 60 120/240 1 3 3 3 3 3 3 25 60 120/240 1 3 | | 15YD | 12 | 50 | 115/230 | | | 1 | 26/662 x 14/350 x 15/381 | 301/137 |
| Reconnectable 3 20YD 16 50 115/230 1 27/686 x 14/350 x 15/381 35 20 60 120/240 1 3 32 32 32 32 32 32 32 33 </td <td></td> <td></td> <td></td> <td></td> <td>Reconnectable</td> <td></td> <td></td> <td>3</td> <td></td> <td></td> | | | | | Reconnectable | | | 3 | | |
| 20YD 16 50 115/230 1 27/686 x 14/350 x 15/381 35 Reconnectable 3 3 3 3 3 3 20 60 120/240 1 3 3 3 3 25 YD 20 50 115/230 1 28/711 x 14/350 x 15/381 38 38 25 K0 120/240 1 3 3 3 3 3 3 3 25 K0 120/240 1 1 30/762 x 14/350 x 15/381 38 38 3 <t< td=""><td></td><td></td><td>15</td><td>60</td><td>120/240</td><td></td><td></td><td>1</td><td></td><td></td></t<> | | | 15 | 60 | 120/240 | | | 1 | | |
| Reconnectable 3 20 60 120/240 1 Reconnectable 3 25YD 20 50 115/230 1 28/711 x 14/350 x 15/381 38 25YD 20 50 115/230 1 28/711 x 14/350 x 15/381 38 25 60 120/240 1 1 1 1 1 25 60 120/240 1 1 1 1 1 1 30YD 25 50 115/230 1 30/762 x 14/350 x 15/381 44 4 30 60 120/240 1 1 1 1 32YD 25 50 Reconnectable 3 30/762 x 14/350 x 15/381 44 32 60 Reconnectable 3 30/762 x 14/350 x 15/381 44 | | | | | Reconnectable | | | 3 | | |
| 20 60 120/240 1 Reconnectable 3 25YD 20 50 115/230 1 28/711 x 14/350 x 15/381 38 Reconnectable 3 3 3 3 3 3 25 60 120/240 1 1 1 1 1 1 25 60 120/240 1 < | | 20YD | 16 | 50 | 115/230 | | | 1 | 27/686 x 14/350 x 15/381 | 352/160 |
| Reconnectable 3 25YD 20 50 115/230 1 28/711 x 14/350 x 15/381 38 Reconnectable 3 3 38 38 38 38 25 60 120/240 1 1 25 60 120/240 1 1 Reconnectable 3 30/762 x 14/350 x 15/381 44 | | | | | Reconnectable | | | 3 | | |
| 25YD 20 50 115/230 1 28/711 x 14/350 x 15/381 38 Reconnectable 3 3 3 3 3 3 25 60 120/240 1 3 3 3 30YD 25 50 115/230 1 30/762 x 14/350 x 15/381 44 30 60 120/240 1 3 44 30 60 120/240 1 44 32 60 Reconnectable 3 30/762 x 14/350 x 15/381 44 | | | 20 | 60 | 120/240 | | | 1 | | |
| Reconnectable 3 25 60 120/240 1 Reconnectable 3 1 30YD 25 50 115/230 1 30/762 x 14/350 x 15/381 44 30 60 120/240 1 30/762 x 14/350 x 15/381 44 32 60 Reconnectable 3 30/762 x 14/350 x 15/381 44 | | | | | Reconnectable | | | 3 | | |
| 25 60 120/240 1 Reconnectable 3 30 60 120/240 1 30 60 120/240 1 32 50 Reconnectable 3 32 60 Reconnectable 3 | | 25YD | 20 | 50 | 115/230 | | | 1 | 28/711 x 14/350 x 15/381 | 389/177 |
| Reconnectable 3 30YD 25 50 115/230 1 30/762 x 14/350 x 15/381 44 30 60 120/240 1 1 30/762 x 14/350 x 15/381 44 32 60 Reconnectable 3 30/762 x 14/350 x 15/381 44 32 60 Reconnectable 3 30/762 x 14/350 x 15/381 44 | | | | | Reconnectable | | | 3 | | |
| 30YD 25 50 115/230 1 30/762 x 14/350 x 15/381 44 30 60 120/240 1 1 32 50 Reconnectable 3 30/762 x 14/350 x 15/381 44 32 60 Reconnectable 3 30/762 x 14/350 x 15/381 44 | | | 25 | 60 | 120/240 | | | 1 | | |
| 30 60 120/240 1 32YD 25 50 Reconnectable 3 30/762 x 14/350 x 15/381 44 32 60 Reconnectable 3 3 3 | | | | | Reconnectable | | | 3 | | |
| 32YD 25 50 Reconnectable 3 30/762 x 14/350 x 15/381 44 32 60 Reconnectable 3 | | 30YD | 25 | 50 | 115/230 | | | 1 | 30/762 x 14/350 x 15/381 | 449/204 |
| 32 60 Reconnectable 3 | | | 30 | 60 | 120/240 | | | 1 | | |
| | | 32YD | 25 | 50 | Reconnectable | | | 3 | 30/762 x 14/350 x 15/381 | 449/204 |
| 35YD 30 50 115/230 1 32/813 x 14/350 x 15/381 50 | | | 32 | 60 | Reconnectable | | | 3 | | |
| | | 35YD | 30 | 50 | 115/230 | | | 1 | 32/813 x 14/350 x 15/381 | 506/230 |
| 35 60 120/240 1 | | | 35 | 60 | 120/240 | | | 1 | | |
| 40YD 30 50 Reconnectable 3 32/813 x 14/350 x 15/381 50 | | 40YD | 30 | 50 | Reconnectable | | | 3 | 32/813 x 14/350 x 15/381 | 506/230 |
| 4060Reconnectable3 | | | 40 | 60 | Reconnectable | | | 3 | | |

Reliable Performance for Every Mobile Power Application



2-7 kW Quiet Gasoline and LP

Designed for tough commercial applications, Quiet Gas[™] Series generators are loaded with quality features. And the Quiet Gas EFI is the first Electronic Fuel Injection generator set in the industry. The Quiet Gas Series features exceptionally low noise and vibration, easy installation, diagnostic capability and digital regulation that keeps voltage and frequency stable as loads change.

The advanced digital control provides extensive diagnostic capabilities by constantly monitoring operation and alerting the user to potential problems. It also assists the operator or service personnel in troubleshooting a variety of operating conditions and service checks.

- Full housing with enclosed muffler
- Lightweight, compact
- Single-side servicing
- Low fuel consumption
- Warranty





5-12 kw Quiet Diesel

The Quiet Diesel Series models are the heavy-duty choice when low noise and low vibration are required. Their revolutionary design makes these generator sets up to 15 dB(A) quieter than other diesel-powered generators, and quieter than most gasoline sets. The unit is totally enclosed, including cooling, muffler and intake systems, for easy installation.



- Self-diagnostic capability
- Top-mounted switches and coolant level check/fills
- Service and maintenance points
- Fully focalized internal mounting system
- UV-resistant paint and water-resistant controls
- Automatic glow plug timing
- Easy installation
- Warranty

6-20 kw Standard Diesel

Standard open diesel generators offer exceptional value with features to match, including smooth operation, increased cooling efficiency and low harmonic distortion.

- Replaceable air cleaner elements
- Battery-charging DC alternator
- Lifting brackets
- Electric fuel pump
- Water-resistant controls
- Glow plugs for reliable all-weather starting
- Flexible installation
- Multiple oil fill/check points
- Fuel filter/water separator optional
- Warranty



🗨 ѕмоотн

"Our Cummins Onan generator is mounted to our mobile dentist tractor/trailer to power an X-ray system, water pumps, drills and air-conditioning. There's no noise, and never an issue. We can concentrate on patients, not on the power equipment!"



6-25 kw Hydraulic

The Cummins Onan Hydraulic Series of generators are designed as a fully integrated power system that includes the hydraulic pump, motor generator, filtration system, oil cooler and reservoir in one complete, compact and lightweight package.

Cummins Onan Hydraulic generators start under full load and run at the rated output, giving you all the power and performance you're paying for.

- High-performance motor-starting capability for heavy loads
- Meets full load capability at 120° F (50° C) ambient conditions
- Designed to provide clean, quiet power with low vibration
- Powder-coated and stainless steel housings
- Easy, single-side serviceability minimizes compartment space requirements
- Multiple air inlet locations for flexible installation and compact size offering several mounting options
- Full power available on the fly
- Best warranty in the industry



12-40 kw Power Take-Off

The Cummins Onan Protec PTO generators are specifically engineered for mobile emergency vehicle use with a field-proven design for high performance and long life. Features include various mounting configurations, bi-directional rotation with radial fan, and remote mountable solid state electronic voltage regulator.



- Capped voltage regulation
- Environmental protection for adverse conditions
- 50/60 Hz switchable
- Brushless exciter
- Double-sealed, pre-lubricated bearings
- Air-cooled with shaft-mounted centrifugal fan
- Skewed stator for low harmonic distortion
- Class H insulation, 180° C temperature rating
- Reconnectable three phase; single phase available
- Best warranty in the industry

About Cummins Onan

Cummins Onan is a brand of Cummins Power Generation, a subsidiary of Cummins Inc. (NYSE: CMI). Cummins Inc. is a global leader that manufactures, distributes and services engines, fuel systems, controls, air handling, filtration, emission solutions and electrical power generation. Headquartered in Columbus, Indiana, USA, Cummins services customers in more than 160 countries through its network of 550 company-owned and independent distribution facilities, and more than 5,000 dealer locations. The Cummins Onan brand is found on generators and products manufactured for the RV, marine, commercial mobile and residential generator markets.

Cummins Power Generation

1400 73rd Ave. NE Minneapolis, MN 55432 USA Phone 1 763 574 5000 Toll-free 1 800 888 6626 Fax 1 763 574 5298 Email www.cumminsonan.com/contact www.cumminsonan.com

©2012 Cummins Power Generation. All rights reserved. Cummins,[®] Onan,[®] the "C" logo and "Performance you rely on.[™] are trademarks or registered trademarks of Cummins Inc. F-1405H (7/12)



ELECTRICAL, MECHANICAL & ENGINEERING DESIGN * MAINTENANCE * INSTALLATION * SALES

20 Egmont Road Henderson WA 6166 Phone: +61 08 9410 5000 Fax: +61 08 9410 5050 Email: admin@cullys.com.au Website: www.cullys.com.au ABN: 30 060 708 590 ECN: 000570

Cummins Onan



Performance you rely on.™